CROSSWAY



CROSSWAY LE City & Line ZEV 12/13 m





4
16







		CROSSWAY LE ZEV CITY & LINE	
		12 m	13 m
LENGTH		12,050 mm	12,965 mm
WIDTH		2,550 mm	
HEIGHT		3,422 mm	
WHEELBASE		6,030 mm	6,945 mm
FRONT / REAR OVERHA	NG	2,725 / 3,295 mm	
FRONT / MIDDLE ACCES	SS HEIGHT	320 / 330 mm	
FRONT / MIDDLE WIDT	E WIDTH LE City: 1,200 mm - LE Line: 800 mm		Line: 800 mm / 1,200 mm
TURNING RADIUS (CURB TO CURB)		8,800 mm	10,025 mm
TURNING RADIUS (WAI	LL TO WALL)	10,680 mm	11,900 mm
APPROACH / DEPARTURE ANGLES		7° / 7°	
MAX. TECHNICALLY PERMISSIBLE GVW* 19,500* kg		00* kg	
MAX. TECHNICALLY PERMISSIBLE AXLE LOADS*	FRONT / REAR (LINE)	7,100 /	12,500 kg
	FRONT / REAR (CITY)	7,500 /	13,00 kg

^{*} Max allowed vehicle axles load and GVW is depending on local regulation in registration country


ENGINE	ELECTRICAL MOTOR		
MAX PEAK POWER	290 KW@ 1200 RPM		
MAX TORQUE	3000 NM @ 0-800 RPM		
MAX CONTINUOUS POWER	185 KW @ 1300 RPM		
MAX CONTINUOUS TORQUE	1650 NM@ 0-800 RPM		
	CENTRAL E-MOTOR DRIVE LINE		

LAYOUT (*)

City




I2m - 34 seats + I UFR



I3m - 40 seats + I UFR

Line



I2m - 42 seats + I UFR



I3m - 48 seats + I UFR

CROSSWAY



CROSSWAY LE City & Line ZEV 12/13 m

BODY AND EXTERIOR EQUIPMENT

- Anticorrosion cataphoretic treatment of the structure and of the body, finished with a polyurethane resin final coat
- LE City: Front door 1,200 mm 2 leaves, middle door 1,200 mm 2 leaves.
- LE Line : Front door 800 mm I leaf,, middle door 1,200 mm 2 leaves
- External rearview mirrors, heated, with electrical control

INTERIOR EQUIPEMENT

- Self-adhesive anti-slip PVC carpet on the floor
- Roof & lateral walls covered by laminated panels
- Separation walls made of laminated panels
- Central platform opposite of the middle door
- Cantilever seats
- Manual ramp for disabled persons

ELECTRICAL EOUIPMENT

- Two batteries 12 V 225 AH
- · Electrical box with circuit breakers
- · Internal and external LED lights
- Fog lights with cornering function
- 24 V and 2x USB sockets on the dashboard

WINDOWS/ THERMAL COMFORT

- · Tinted simple glass with 5 opening units
- Convector heaters for the passenger's compartment
- Electrical defrosting of the windshield
- · Electric independent heater

DRIVER'S COMPARTMENT

- Adjustable driver's seat with air suspension, headrest,
 3 pts safety belt
- · Front sun visor with electrical control
- · Driver's cabin with door
- Driver's box with lock
- On board computer
- Digital tachograph
- · Movable cluster with driver cabin

ADAS/GSR equipment including

- Blind spot info system
- Moving off info system
- Reverse camera
- Intelligence speed assist (speed limit display)
- · Driver drowsiness attention warning
- · Alcohol interlock preparation

OPTIONAL

- Ski carrier preparation
- Towing device preparation
- Towing device
- Other combination of doors available -Please see with our commercial representative

OPTIONAL

- Electrical ramp for disabled persons
- Step Bus
- LE City: Central platform right side
 Central platform for 2 UFR

OPTIONAL

- · Warning lights with open doors
- Reverse sensors
- · 12 V socket on the dashboard
- FMS plug

OPTIONAL

- Double glasses of the lateral windows, driver's window and passengers' doors
- A/C with or without heating
- HVO-Diesel or Bi-mode independent
 heater
- · Reinforced Convector heaters
- · Electrical defrosting of the front door

OPTIONAL

- · Driver's seat with heating system
- · Driver's refrigerator
- · Additional driver's heater
- Driver's A/C

OPTIONAL

- Blind spot info system (Left side)
- · Alcohol ignition interlock device

MOTOR

· Siemens central motor

CHARGING

Overnight charging through plug CCS Combo 2

BATTERY PACKS

FPT MVi Energy - 7 packs* (485 kWh)
 *7 packs not possible for LE Line 13m

REAR AXLE

- Single reduction hypoid rear axle
- 6.17 Rear axle ratio 6 x 37

FRONT AXLE / STEERING

- Front axle with independent wheels suspension
- Worm-type steering with integrated power steering

SUSPENSION

- · Full air suspension ELC with self- leveling sensor and kneeling
- Front: 2 combined air springs/2 shock absorbers/1 leveling sensor
- Rear: 4 air springs/4 shock absorbers /1 stabilization bar/2 leveling sensors
- Kneeling

COMPRESSED AIR

Electric air compressor TX02 5.5 kW

BRAKES

- EBS, ESP
- Pneumatic service and emergency braking system with two independent air circuits
- Brake discs, front and rear, with floating callipers and ABS
- Pneumatic parking brake, operating on the rear wheels

TYRES AND WHEELS

- 275/70 R 22.5 tyres
- Tyres pressure monitoring

OPTIONAL

- Opportunity fast charging via Pantograph bottom up / Top down
- Please check availability on models with our commercial representative

IVECO

Drive the road of change

OPTIONAL

FPT MVi Fnergy ·

- 5 packs / 346 kWh (LE City)
- 6 packs / 416 kWh

OPTIONAL

Lifting of the vehicle's suspensions